

## RADWIN Indoor Unit

IDU-C Series



RW-7200-2000

### Product Description

IDU-C is a carrier class indoor unit that provides 2 x Ethernet ports, 1 x SFP Port and Dry Contacts interface.

IDU-C supports wide range DC power feeding. IDU-C is a scalable solution that is compatible with RADWIN PtP radio portfolio.

### Product Highlights

- Carrier class indoor unit
- Wide range DC power feeding
- Ease of operation and maintenance

## Product Specifications:

Ethernet Interface	
PoE interfaces	1
Ethernet ports	2x10/100/1000 BaseT; Auto-Negotiation (IEEE 802.3u); Framing/Coding IEEE 802.3
Connector	RJ-45
Impedance	100Ω
SFP Interface	1xGbE SFP Port
VLAN Support	Transparent
Maximum Frame Size	2048 Bytes
Bridge	Layer 2, self-learning of up to 1024 MAC addresses (IEEE 802.1Q), Hub/Bridge selectable
Dry Contact Alarms	
Dry Contact Interface	4 Outputs + 4 Inputs; configurable by RADWIN Manager
Mechanics	
Dimensions	44(w) x 5(h) x 21(d) cm
Weight	1.2 kg / 2.65 lbs
Power	
Power Feeding	Dual redundant power feeding; -20 to -60VDC 2.5A
Power Consumption	<10W
Environmental	
Operating Temperatures	0°C to 50°C / 32°F to 122°F
Humidity	Up to 90% non-condensing
Safety	
TUV	IEC/EN 60950-1, UL 60950-1, CAN/CSA-C22.2 No. 60590-1
EMC	
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4
FCC	Class B Part 15 Subpart B
CAN/CSA	ICES 003 CISPR 22 Class B
AS/NZS	CISPR22 Class B

### Ordering Info

Part Number: RW-7200-2000

Description: IDU-C, 2 x Ethernet Ports, 1000 BaseT Interface and 1 x SFP Port.