

DHI-LCH65/75/86-MC410-B

65/75/86" UHD Smart Interactive Whiteboard



- 65/75/86-inch 4K DLED display with Zero Air Gap technology that delivers a clear image in sharp, vivid colors.
- Built-in 1080p camera and 2 microphones that produces excellent quality visual and audio communication.
- Wireless screen sharing from multiple devices with an intuitive, easy-touse system.
- Quick file sharing by scanning a QR code, with easy file encryption for added privacy and security.
- · Supports mainstream Android applications with Android 9.0.
- Optional OPS module to support Windows, dual-system switchable.

System Overview

With Android 9.0 embedded in its design, Dahua Smart Interactive Whiteboard has powerful processing capabilities with its 4-core CPU, 4-core GPU, and 4G RAM 32G storage capacity. Equipped with a high-precision infrared frame with a 2 mm identification diameter and a 4K high-definition DLED module, this whiteboard will give you an extraordinary experience whether you are writing, controlling or displaying content. It features video conferencing, wireless screen sharing, file management, HD display, scan & go and more. Rely on this whiteboard to modernize your meeting room, and make your meetings more efficient.

Functions

Built-in Camera with Wide FOV

The built-in camera support a maximum resolution of 1080p@30 fps. It supports live view, and has an ultra-wide field of view, capturing vivid details even in relatively large meeting rooms.

Wireless Screen Sharing

In addition to basic file share, wireless screensharing and reverse control, it also supports screen grouping (multiple transmission), real-time transmission of wireless camera picture and sound from the mobile phone, host mode (for overall authority control) and split-screen mode that displays up to 4 spilts on the same screen.

Hidden Antenna Design

The Wi-Fi and hotspot antenna has a front hidden design, which is not only beautiful and simple, but also ensures the stability of the signal strength when using a flush mount.

Real Writing Experience

Designed to enhance the writing experience. With our zero air gap glass bounding, high accuracy and low latency touch technology, writing on the whiteboard feel natural, similar to the actual writing experience.

Easy to Share

Enhances the experience of sharing files by scanning a code. It automatically determines the device network to readily share the QR code across the extranet and the intranet. QR code encryption and extraction are also featured, providing privacy and data security through the required entry of a 6-digit random password for verification.

Technical Specification		
Built-in System		
Operating System	Android 9.0	
CPU	Quad-core A55	
RAM	4 GB	
ROM	32 GB	
LCD Panel		
Panel Dimensions	65-inch;- 75-inch; 86-inch	
Brightness	65-inch: 350 cd/m2; 75-inch: 350 cd/m2; 86-inch: 35 cd/m2	
Contrast	1200: 1	
Resolution	3840 (H) × 2160 (V)	
Aspect Ratio	16: 9	
Backlight	DLED	
Lifespan	30,000 hours	
Viewing Angle	H: 178°; V: 178°	
Touchscreen		
Touch Technology Type	Infrared touch technology	
Touch Points	20	
Writing Mode	Finger + Pen	
Response Time	<10 ms	
Valid Touch	2 mm	
Touch Accuracy	±1 mm	
Communication Mode	USB	
Camera		
Max. Resolution	1080p @30fps	
FOV(H×V)	80.4° × 64.6°	
Speaker		
Built-in Speaker	2	
Power	Full frequency: 15 W × 2	
Microphone		
Pick-up Distance	Far-field sound pickup: 6 m-8 m (19.69 ft-26.25 ft)	
Number of Microphones	2	
Other Features	AGC, Echo Cancellation	
Function		
Operating System of External Module	Optional Windows; Android	
WiFi	Dual-band 2.4G/5G	
Wi-Fi Hotspot	Dual-band 2.4G/5G; supports enabling Hotspot and Wi-Fi at the same time	

Device Ports

Network Port	RJ-45 (10\100\1000M)	
Wi-Fi	1 × Wi-Fi(2.4G/5G); 1 × Hotspot(2.4G/5G)	
USB	3 × USB3.0 (1 side, 2 back);	
RS-232	1 × RS-232	
Video Input	1 × HDMI IN(up to 4K/60)	
Audio Output	1×3.5 mm (Line Out);	
Light Sensor	1	
IrDA	1 (IR remote)	
Others	1 × Touch(USB Type-B); 1 × Micro USB(debug)	

General

Power Supply 100–240 VAC, 50/60 Hz	General		
Product Dimensions	Power Supply	100–240 VAC, 50/60 Hz	
Packaging Dimensions 42.13" × 8.86") 75-inch: 1810mm × 1189mm × 235mm (71.26" × 46.81" × 9.25") 86-inch: 2056mm × 1334mm × 235mm (80.94" × 52.52" × 9.25") Operating Temperature 0 °C to +45 °C (32 °F to +113 °F) Storage Temperature -20 °C to +60 °C (-4 °F to +140 °F) Operating Humidity 10%–90% Storage Humidity 10%–90% Product Material Metal casing Glass Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Product Dimensions	× 3.43"); 75-inch: 1707mm × 1066mm × 87mm (67.2" × 41.97" × 3.43"); 86-inch: 1953mm × 1205mm × 87mm (76.89" × 47.44"	
Storage Temperature -20 °C to +60 °C (-4 °F to +140 °F) Operating Humidity 10%–90% Storage Humidity 10%–90% Product Material Metal casing Glass Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black Gross Weight 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Packaging Dimensions	42.13" × 8.86") 75-inch: 1810mm × 1189mm × 235mm (71.26" × 46.81" × 9.25") 86-inch: 2056mm × 1334mm × 235mm (80.94" ×	
Operating Humidity 10%–90% Storage Humidity 10%–90% Product Material Metal casing Glass Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black Gross Weight 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Operating Temperature	0 °C to +45 °C (32 °F to +113 °F)	
Storage Humidity 10%–90% Product Material Metal casing Glass Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black Gross Weight 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)	
Product Material Metal casing Glass Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black Gross Weight 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Operating Humidity	10%-90%	
Glass Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Storage Humidity	10%–90%	
Casing Color (Frame/Rear) Bottom: Silver; top/left/right: black 65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Product Material	Metal casing	
65-inch: 46 kg (101.4 lb) 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Glass		
Gross Weight 75-inch: 65 kg (143.3 lb) 86-inch: 77 kg (169.8 lb)	Casing Color (Frame/Rear)	Bottom: Silver; top/left/right: black	
Installation Wall mount; floor-standing	Gross Weight	75-inch: 65 kg (143.3 lb)	
	Installation	Wall mount; floor-standing	

Smart Interactive Whiteboard Series | DHI-LCH65/75/86-MC410-B

Ordering Information			
Туре	Model	Description	
65–inch Smart Interactive Whiteboard With Camera	DHI-LCH65- MC410-B	Smart Interactive Whiteboard DHI-LCH65-MC410-B	
75—inch Smart Interactive Whiteboard With Camera	DHI-LCH75- MC410-B	Smart Interactive Whiteboard DHI-LCH65-MC410-B	
86–inch Smart Interactive Whiteboard With Camera	DHI-LCH86- MC410-B	Smart Interactive Whiteboard DHI-LCH86- MC410-B	
	DHI-PKP-IPOA	Smart Pen (optional)	
	DHI-PKP-WPOB	Wireless Screen Sharing Cable (optional)	
	DHI-MC-PI5681IL	PC module I5–6400 + 8 GB + 128 GB (optional)	
	DHI-MC-PI7682IL	PC module I7–6700 + 8 GB + 256 GB (optional)	
	DHI-MC-PI5881IL	PC module I5 8 GB + 128 GB (optional)	
Accessories	DHI-MC-PI5882IL	PC module I5 8 GB + 256 GB (optional)	
	DHI-PKC-MS0A	65"/75" Interactive Whiteboard Mobile Stand (optional)	
	DHI-PKC-MS1A	86" Interactive Whiteboard Mobile Stand (optional)	
	DHI-PKC-MSOC	65"/75" Interactive Whiteboard Liftable Mobile Stand (optional)	
	DHI-PKC-MS0B	65"/75" Interactive Whiteboard Mobile Stand (optional)	
	DHI-PKC-MS1B	86" Interactive Whiteboard Mobile Stand (optional)	

Installation

