

EXRP-22En Two-Radio Ultra-Thin 802.11n Access Point with Connectors for External Antennas


The Extricom Architecture

- Extremely easy to deploy and grow: No cell planning required.
- Zero-Handoff between access points (voice) and no Edge-User-Effect (data).
- Supports channel separation between legacy and 802.11n devices.
- Supports channel separation between services e.g. voice and data.
- Most suitable architecture for 802.11n: channel bonding, optimal MIMO capacity.

Extricom's exclusive EXRP-22En Ultra-Thin™ Access Point brings a Two-Radio '802.11n' solution to the market place. The EXRP-22En is ideal for clients with bandwidth intensive applications that are looking for high capacity and throughput from their WLAN, in a competitive package. The EXRP-22En has the ability to use external antennae connectors, rather than the internal integrated antennas.

The EXRP-22En is a radio access device and part of Extricom's innovative Channel-Blanket™ architecture. Attached to the Extricom switch, the Extricom Access Points create two wireless blankets without running any software and without the need for configuration. Interference between the access points is completely eliminated by the integrated switch intelligence. Mobile devices traversing the blanket are attached to one homogeneous network and are associated with the switch and not to a particular AP, ensuring they never disconnect.

The Extricom EXRP-22En is equipped with the latest best-of-breed silicon and radio modules. The most advanced radio layer features provided are Transmit Beam Forming (TxBF), Space-Time Block Code (STBC), Low Density Parity Check (LDPC), Maximum Likelihood (ML) detection, Maximum Ratio Combining (MRC) and Cyclic Delay Code (CDC).



Features and Benefits

Guaranteed Service Level Agreement

EXRP-22En enables physical separation between different services (e.g. video, voice and data) by assigning different frequency channels to services. Physical separation between very slow devices e.g. 802.11b wireless clients and very fast devices such as two streams 802.11n wireless clients overcomes 'the weakest link' effect, detrimental to aggregate network throughput. EXRP-22En AP deployment density delivers blanket seamless coverage and a guaranteed communications rate everywhere.

Ease of Installation & Zero Configuration

Extricom Ultra-Thin AP deployment does not require cell planning and facilitates true plug-and-play deployment. EXRP-22En is software free hence requires absolutely no configuration.

External antennas & Standard PoE

The EXRP-22En is plenum-rated and equipped with multiple RP-SMA connectors for external antennas, and can be mounted on wall, ceiling or outdoors in weather proof enclosures. EXRP-22En is 802.03af PoE (Power over Ethernet) compliant. Since the EXRP-22En is highly energy efficient, both radios can operate concurrently out of the given energy budget of 8021.af.

Immune to MIMO Coverage Variability

EXRP-22En employs Extricom's unique patent pending technology for improved transmission on MIMO deployments for reliably high throughput and black hole free MIMO blanket coverage. All APs receive traffic on the same channel. As a direct result, the Extricom blanket WLAN provides uplink path diversity for lower delay latency and higher uplink throughput.

Advanced 802.11n enhancements

The EXRP-22En is equipped with latest physical layer (radio) technologies which directly improves rate-over-range performance (LDPC, TxBF and MLD).



Key Features

- Dual-Radio Access Point with connectors for external antennas - works in mixed 802.11 a/b/g/n environment.
- Up to 300 Mbps air rate (Up to 200Mbps TCP traffic) with 2x2:2 Spatial Stream MIMO
- Transmit Beam forming (TxBF) for signal phase alignment and improved range*
- Space Time Block Cycle (STBC) provides added robustness for an environment where there are multiple transmit chains and only a single receiver chain*
- Low Density Parity Check (LDPC) technology provides improved performance in error detection and correction*
- Maximum Likelihood (ML) detector to achieve higher accuracy demodulation
- Maximal Ratio Combining (MRC)
- Rx Peak Detection for interference detection, providing better performance in environments with a high level of interference
- WEP, TKIP and AES hardware encryption
- Zero AP-to-AP Handoff Delay
- Link Resilience with AP Path Diversity
- Anti-Breach Security and Built-in Rogue AP Detection
- Zero-Configuration Device
- Standard 802.3af PoE on single cable supports full-rate on all radios concurrently
- Multi-layered security including standards-based WPA2 security and rogue detection
- Integral Hanging brackets, and optional ceiling mounted brackets.

* Future firmware upgrade required.

WLAN Standards		Antenna Specifications				
WLAN	IEEE 802.11n, 2.4GHz and 5GHz IEEE 802.11g, 2.4GHz (Pure mode, mixed mode) IEEE 802.11b, 2.4GHz (Short/long preamble support) IEEE 802.11a, 5GHz	Per each Radio	The number of antennas matches the number of streams - two connectors for external antennas.			
Spectrum		Regulations Approval*				
Number of simultaneous channels	Up to two simultaneous 802.11a/b/g/n channels	Safety	UL 60950-1 EN 60950-1 IEC 60950-1			
Operating Frequencies	2.412 – 2.484 GHz 5.180–5.825 GHz	EMC	FCC Part 15 class B EN 331 489 VCCI Technical Requirements, V-3/2001.04			
Supported Rates (Mbps)		Radio (including modular approval)	FCC Part 15 C and FCC Part 15 E EN 330 328 EN 331 893 Japan Type Certificate: Article 2, clause 1 FCC15.407 EN 301 893 (v1.6.1)			
802.11a	6, 9, 12, 18, 24, 36, 48, 54	*Regulatory approvals are in process.				
802.11g	1, 2, 5.5, 11, 6, 9, 12, 18, 24, 36, 48, 54	Physical Properties				
802.11b	1, 2, 5.5, 11	Dimensions (WxHxD)	196 x 42 x 125 mm 7.7 x 1.6 x 4.9"			
802.11n	20MHz, SGI: MCS 0-7 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, MCS 8-15 14.4, 28.9, 43.3, 57.8, 86.7, 115.6, 130, 144.4 MCS 16-23 21.7, 43.3, 65, 86.7, 130,173.3,195, 216.7 40MHz, SGI: MCS 0-7 15, 30, 45, 60, 90, 120, 135, 150 MCS 8-15 30, 60, 90, 120, 180, 240, 270, 300 MCS 16-23 45, 90, 135, 180, 270, 360, 405, 450	Weight	0.6 kg (1.32 lbs)			
Transmitter Power (Max)		Installation Options	Horizontal (desktop), Vertical (wall mount) or Top (Ceiling)			
802.11n	19 dBm	Power	PoE (IEEE 802.3af) Power Supply (optional): 48VDC			
802.11g/b	20 dBm	Environmental				
802.11a	19 dBm	Operational	Temperature: -5°C to +55°C (23°F to 131°F) Humidity: 0% to 95%, non-condensing			
Rogue AP Detection		Storage	Temperature: -20°C to +70°C (-4°F to 158°F) Humidity: 0% to 90%, non-condensing			
Infrastructure	Optional chosen radio on each AP	Ordering Information				
Functionality	Automated, continuous monitoring, ensures fast detection of rogue AP	EXRP-22En	Extricom Two-Radio Ultra-Thin Access Point with two 802.11 a/b/g/n dual streams radios with connectors for external antennas.			
Additional Features	Configurable "white list" of allowed BSSIDs	Related Products				
		Product	Total No. of Radios	No. of radios for each Spatial Streams category		
				Single stream	Dual streams	Triple streams
		EXRP-33n	3	-	1	2
		EXRP-32n	3	-	3	-
		EXRP-22n	2	-	2	-
		EXRP-22En*	2	-	2	-
		EXRP-30n	3	1	2	-
		EXRP-40En*	4	2	2	-

*The AP consists of a metal enclosure with connectors for external antennas (not included)

About Extricom:

Extricom is a manufacturer of 4th generation enterprise wireless LAN solutions, based on its Channel Blanket™ technology. While adhering to the 802.11 a/b/g/n standard, Extricom's patented, Interference-Free architecture takes a completely new approach to the way the infrastructure is deployed. The Channel Blanket topology provides wire-like reliability, high throughput, seamless mobility, unparalleled noise immunity, and is easy to install and maintain. In an era of intensive wireless usage powered by the market explosion of smart phones, iPads, iPods, tablets and other communication devices, voice, data, video, and location services are delivered with an always-on, robust and mobile Wi-Fi connection to any client, in any environment. Extricom Interference-Free™ WLAN is purpose-built to slash wireless complexity and future-proof your network for tomorrow's multi-service demands.

Extricom solutions are in use by customers operating in numerous industries worldwide, including Education, Healthcare, Manufacturing, Logistics and Warehousing, Retail and Public Venues. They have discovered the uncompromising performance, reliability and ease of ownership that are the hallmark of the Extricom WLAN.

Extricom serves its growing global customer base through offices in the USA, Europe and Japan, and by working with a global network of distributors and partners.

For more information, visit us at www.extricom.com.