Product Datasheet Product ID: NB-NBEAM19



NanoBracket[®] for NBE-M5-19

BRACKET FOR NANOBEAM® M5-19 AND 5AC-19

NanoBracket for NBE-M5-19 is our 2nd Generation mounting system for 5GHz/19dBi NanoBeam CPE from UBNT. This NanoBracket has a solid base made of die cast aluminum and allows for 140° of smooth and precise adjustment in azimuth, elevation and rotation using our original ball hinge.

Large mounting surface and all stainless steel hardware make the overall robustness of the bracket SOLID.



TECHNICAL DATA

Materials	Bracket - UV stabilized and weather resistant ABS plastic Holder - ADC 12 Hardware - Stainless Steel
Flame Rating	UL 94 HB
Pole Mounting Diameter	50-70 mm
Wall Mounting	Yes
Operating Temp.	-30 to + 60 °C
Wind Survival	120 Km/h
Weight	0.308 Kg / 0.68 lbs – single unit incl. package 16,4 Kg / 36.16 lbs – carton (50 units)
Single Unit	Retail Box: $15 \times 9 \times 9$ cm
50 units	Carton Box: 48 × 34 × 47 cm

COMPATIBLE WIRELESS PLATFORMS


Ubiquiti Networks™


NanoBeam® 5AC-19 NanoBeam® M5-19

PACKAGE CONTENTS

Bracket Body Holder Screw 3,5 x 45 mm (4 pcs) Wall Plug (4 pcs) Hose Clamp (1pcs)

PRODUCT DIMENSIONS





RF elements® and NanoBracket® are trademarks of RF elements s.r.o., Humenne, Slovakia.

© RF elements 2015

NanoBracket® Rev JUNE-2015

www.rfelements.com

All rights of respective trademark owner reserved.

www.4Gon.co.uk info@4gon.co.uk Tel: +44 (0)1245 808295 Fax: +44 (0)1245 808299