



BridgeWave
COMMUNICATIONS

FLEX4G-3000

80 GHz Multi-Gigabit Ethernet, CPRI, and SONET/SDH Wireless Backhaul for 4G/LTE Networks

As mobile data consumption increases exponentially, operators are looking for a backhaul solution that provides the lowest Total Cost of Ownership with the flexibility to easily scale to meet tomorrow's bandwidth demands. BridgeWave's Flex4G-3000 with support for backhaul capacity of up to 3.2 Gbps per radio while operating in spectrally efficient 256QAM modulation has been designed to alleviate the strain of backhaul connections by combining advanced radio and modem capabilities with carrier-grade Ethernet, CPRI, and SONET/SDH features at the lowest total cost of ownership.

BridgeWave's highly integrated RF and spectrally efficient signal processing techniques provide for the longest link distances, while maintaining multi-gigabit speeds in narrow channel bandwidths. Further enabling future-proof transport, Flex4G-3000 allows operators to flexibly provision links across multiple network topologies including mixing Ethernet, CPRI, and SONET/SDH traffic.

Carrier Ethernet services are provided through the use of an integrated low-latency switch supporting jumbo frames and advanced Ethernet functionality including Quality of Service (QoS), VLAN support, Provider Bridge (Q-in-Q), Radio Link Aggregation (RLA) and Ethernet OAM management. Flex4G-3000 provides comprehensive timing support required for 4G/LTE deployments including Synchronous Ethernet and IEEE1588v2 with hardware-based timestamping for one-step or two-step clocks.

With ultra-low power consumption and PoE power along with direct DC power, Flex4G-3000 provides all of the above in an environmentally friendly, compact and lightweight, zero-footprint all-outdoor solution.

Flex4G-3000 leverages BridgeWave's expertise in providing high reliability gigabit millimeter wave wireless solutions. BridgeWave has delivered tens of thousands of gigabit millimeter wave radios worldwide.



FLEX4G-3000
shown with 12" (30cm)
Antenna

WIRELESS VIRTUAL FIBER SOLUTIONS FOR:



MOBILE BACKHAUL

Future-proof multi-gigabit backhaul for next generation 4G/LTE networks.



SERVICE PROVIDER

High Capacity business services, fiber extensions, cellular/Wi-Fi/WiMAX backhaul, redundant fiber overlays, mesh.



EDUCATION

High-performance seamless campus connectivity, Wi-Fi and security camera backbone.



ENTERPRISE

Leased line replacement, LAN extensions, server centralization, remote data storage and backup.



GOVERNMENT/MUNICIPALITIES

Inter-building connections, Video surveillance systems, traffic control and monitoring, Wi-Fi/4.9 GHz backhaul.



HEALTHCARE

Secure, HIPAA-compliant medical office, lab network access, real-time imaging & records, application connectivity.

PERFORMANCE:

- 3.2 Gbps data rate per 1+0 radio and up to 6.4 Gbps per 2+0 radio
- Adaptive Code Modulation from BPSK through 256QAM
- 250 MHz or 500 MHz RF channel bandwidths
- Highest bit/Hz spectral efficiency at the longest link distances
- Outstanding RF performance benefiting from highly integrated architecture
- RF channel tuning across the entire 70/80 GHz band in 250 MHz steps
- Automatic Transmit Power Control
- Zero-footprint ODU with low power consumption and Power-over-Ethernet

CARRIER-GRADE:

- Carrier Ethernet services enabled via built-in low-latency switch
- Quality of Service (802.1p) traffic prioritization, VLAN (802.1q), Provider Bridge (Q-in-Q 802.1ad)
- Synchronous Ethernet per G.8261 and G.8262 and G.8264
- PTP per 1588v2 – Transparent, Boundary and Ordinary clock support
- Ethernet OAM support per 802.3ah, 802.1ag and Y.1731
- 1+0, 1+1 HSB, and 2+0 configuration support
- Radio Link Aggregation
- SONET/SDH & CPRI interfaces

SECURITY:

- Highly secure narrow beamwidth antennas
- FIPS-certified AES Encryption provides the ultimate in data protection at full line rate gigabit speeds with minimal latency



PROVEN RELIABILITY:

- Based on proven design – tens of thousands of systems deployed worldwide
- Rigorous HALT/HASS testing
- Carrier-grade 99.999% availability



BridgeWave
COMMUNICATIONS

FLEX4G-3000 SPECIFICATIONS

FREQUENCY	Range: 71 – 76 GHz / 81 – 86 GHz T/R Spacing: 10 GHz, FDD operation Channelization: Software selectable channels in 250 MHz increments per ITU-R F.2006 Recommendation Stability: ± 10 ppm						
CONFIGURATIONS	1+0 Non-Protected; 2+0 Dual Path Transmission utilizing Orthogonal Mode Transducer (OMT) 1+1 Hot Standby - dual antenna or single antenna with symmetrical coupler or asymmetrical coupler						
DATA RATE	Up to 3.2 Gbps in 1+0 configuration or 6.4 Gbps in 2+0 configuration						
F.E.C	Reed-Solomon						
MODULATION	BPSK	QPSK	16QAM	32QAM	64QAM	128QAM	256QAM
RF CHANNEL BANDWIDTH & SYSTEM GAIN	250 MHz / 500 MHz	250 MHz / 500 MHz	250 MHz / 500 MHz	250 MHz / 500 MHz	250 MHz / 500 MHz	250 MHz / 500 MHz	250 MHz / 500 MHz
User Data Rate	200 / 400 Mbps	400 / 800 Mbps	800 / 1600 Mbps	1000 / 2000 Mbps	1200 / 2400 Mbps	1400 / 2800 Mbps	1600 / 3200 Mbps
Tx Power Output	+17 dBm	+17 dBm	+15 dBm	+14 dBm	+13 dBm	+12 dBm	+10 dBm / +9 dBm
Rx Sensitivity for 10^{-6} BER	-73 / -70 dBm	-70 / -67 dBm	-62.5 / -59.5 dBm	-59 / -56 dBm	-56 / -53 dBm	-53 / -50 dBm	-49.5 / -46.5 dBm
INTERFACES	Ethernet: 4 x SFPs for 1000Base-SX, -LX, or 10/100/1000Base-T + 1 x 10/100/1000Base-T RJ-45 SDH/SONET/CPRI: 1 x SFP (single mode fiber) SDH/SONET: 1 x STM-4/OC-12 (622.08 Mbps) or 1 x STM-16/OC-48 (2488.32 Mbps) CPRI: 1 x Option 1 to 3 (614.4 Mbps to 2457.6 Mbps)						
NETWORKING	Quality of Service per IEEE 802.1p, DSCP and port based Scheduling: 8 queues allowing user configurable Strict Priority or Shaped Deficit Weighted Round Robin (SDWRR) MEF compliant traffic policing (two rate, three color scheme) VLAN per IEEE 802.1q, up to 4096 VLANs Provider Bridge Q-in-Q per IEEE 802.1ad Synchronous Ethernet (SyncE) per ITU-T G.8261, G.8262 and DNU section of G.8264 Precision Time Protocol (PTP) per IEEE 1588v2 – Transparent, Boundary and Ordinary clock support Congestion Management: WRED and Tail Dropping Ethernet Protection: Ring per G.8032, Linear per G.8031, MPLS-TP protection (G.8131 & G.8132) Maximum Ethernet frame length: Jumbo packets up to 10,000 bytes MAC Layer: Supports MAC Learning, MAC Switching, MAC Ageing Multiple Spanning Tree Protocol (MSTP), Rapid Spanning Tree Protocol: (RSTP) Link State Propagation: Rapid Link Shutdown (RSP) supports remote port LSP Radio Link Aggregation						
LATENCY	Dependent on configuration, as low as 13 μ Sec						
SECURITY	Inherently secure ultra-narrow beamwidth antennas for low probability of detection and interception Option: FIPS-197 certified 256-bit AES Encryption (export controlled)						
MANAGEMENT	Web-based (HTTP/HTTPS) embedded management agent; Console Interface (CLI/SSH), IPv6 protocol stack SNMP Support: MIB-II and BridgeWave enterprise MIB, SNMP V1, V2, V3 SysLog (RFC 3164, RFC 3195) event support, RADUIS RFC2865 client support Ethernet OAM per 802.3ah (Link OAM), 802.1ag (Configuration Fault Management), Y.1731 (Performance Monitoring) Loopbacks: Ethernet (per port, per direction), Local Modem Test						
POWER	48 VDC nominal input, \pm (42.5 to 57) VDC input to POE or \pm (37.5 to 57) VDC direct DC input; 48 watts max power consumption Max POE Cat5E/6 cable length is 328 ft (100 m) Max DC cable length with 12 AWG cable is 650 ft (198 m) and with 14 AWG cable is 400 ft (122 m)						
SIZE & WEIGHT	13.1" w x 11.6" h x 4" d (33.4 cm x 29.5 cm x 10.2 cm); 9.6 lbs (4.4 kg)						
ENVIRONMENTAL	Operating Temperature: -33°C to +55°C (-27°F to +131°F) per EN 300 019-2-2 Class 2.3 Humidity: 100% all-weather operation Operating Altitude: Up to 4,500m (14,764 ft) Water Ingress: NEMA 4X (IP66) RoHS & WEEE Compliant						
REGULATORY	RF Certifications: U.S. FCC Part 101, EN 302 217-3; RF Exposure : meets FCC 1.310 General Population & EN 62311 RF MPE limits Safety: CE Mark; 60950-1; Corrosion : EN 60950-22 EMC/EMI: EN 301 489-1 and -4; FCC Part 15 Class B Surge & Immunity: IEC61000-4-5, GR-1089, K.21, K.44						
ANTENNAS	12" (30cm) Parabolic, 44dBi gain, 0.8° beamwidth or 24" (60cm) Parabolic, 51dBi gain, 0.4° beamwidth						

© 2015 BridgeWave Communications. All rights reserved. BridgeWave, the BridgeWave logo, Flex4G, FlexPort, Backhaul Evolved, PicoHaul, AdaptRate and AdaptPath are trademarks of BridgeWave Communications in the United States and certain other countries. All other brands and products are marks of their respective owners. BridgeWave strongly recommends that a link analysis be performed to ensure the system meets the individual application requirements. BridgeWave reserves the right to change specifications and features listed herein without notice or obligation. 09/15

040-57063-02

www.4Gon.co.uk info@4gon.co.uk Tel: +44 (0)1245 808295 Fax: +44 (0)1245 808299