MBX Mini



Good things come in small packages

Small is the new mighty.

Bring your deployments to life with the versatility of the MBX Mini. It's just as brilliant as any other MBX device we have to offer. So connect your devices to the PoE enabled LAN ports to provide network simplicity as well as IEEE 802.1X port authentication. This MBX Mini has the power to achieve it all.



One. Two. Three. Four.

We know fast connections are critical to achieving great things. Its dual-band Wi-Fi and 5G capabilities ensure you experience the fastest available network. If the dual embedded cellular WANs are not enough, the MBX Mini can be expanded to FOUR cellular WANs by simply connecting it to our MAX Adapters via the dual USB ports.






Making hard to manage feel like hardly managing.

With this FusionSIM-ready router, you can say goodbye to switching and managing multiple SIMs via the router. FusionSIM offers remote provisioning of SIM profiles from anywhere in the world. Managing made easy, ready when you are!

MBX Mini



Specifications

WAN Interface	2x Embedded Cellular Modems with Redundant SIM Slots	Power Consumption	45 W (max.)	
	2x GE 2x USB 2.0 Interface	Dimension	7.32 x 8.05 x 1.61 inches 186 x 204.5 x 41 mm	
LAN Interface	4x GE	Weight	4.19 pounds / 1.9 kg	
Wi-Fi Interface	802.11ac/a/b/g/n, 1166 Mbps 2x2MIMO Wi-Fi WAN and/or AP Simultaneous Dual-Band	Operating Temperature	-40°- 149°F / -40°- 65°C	
		Humidity	15% – 95% (non-condensing)	
Router Throughput	2.5 Gbps	Certifications	FCC, CE, RoHS, E-Mark, PTCRB Shock and Vibration Resistance: EN 61373:1999 IEC 61373:1999 Railway Applications: EN 50155 Electromagnetic Compatibility: EN 61000	
PepVPN Throughput (No Encryption)	600 Mbps			
PepVPN Throughput (256-bit AES)	500 Mbps			
5G Cellular Data Rate (Downlink/Uplink)	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	Package Content ³	MBX Mini, PSU 180W (ACW-630), 4x Dual-Band Wi-Fi Antennas (ACW-341) 1x QMA to SMA Adapter (for GPS).	
SpeedFusion features	Hot Failover, WAN Smoothing, Bandwidth Bonding, Bandwidth Overflow		1x GPS Antenna (ACW-232), Power cord, 1 Pair of Ear L-Mounts kit (ACW-756), Screw set of Ear L-Mounts kit.	
Number of PepVPN SpeedFusion Peers	2/201		3pin Terminal Block Connector (Ignition Sense), 4pin Terminal Block Connector (Power Supply).	
Recommended Users	50-500			
Antenna Connectors	8x QMA Cellular Antenna Connectors 1x QMA GPS Antenna Connector		Rubber Foot Pad set	
	4x RP-SMA Wi-Fi Antenna Connectors	Warranty	1-Year Limited Warranty	
Power Input	DC Jack / Terminal Block: 12-56 V	US Carrier Certifications	Verizon ⁴ , T-Mobile ⁴ , AT&T	
Power Output	Up to 4x 802.3at PoE ²			

¹ Requires a license to increase the maximum number of PepVPN/SpeedFusion Peers. Several options are available based on the model 5, 10 or 20 peers (PVN-LC-05, PVN-LC-10, PVN-LC-20). ² 1x 54V DC input is needed for all 4x LAN ports to have 802.3at PoE. ³ *Cellular antennas not included. To enhance the MBX Mini, Mobility and Maritime antennas are recommended. ⁴ Certification Pending.

Ordering information

Product Code	Description	Embedded Modems	Carrier/ Categories	5G Bands	LTE Bands
MAX-MBX-MINI-5GH-T	MBX Mini	2	America/5G	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79 5G (SA) Sub 6Ghz: n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71
MAX-MBX-MINI-5GD-T Feature Add-or	MBX Mini	2	Global/5G	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n20, n28, n38, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71

Product Code	Description
PVN-LC-05	Up to 5 SpeedFusion Bonding License Key for MBX Mini
PVN-LC-10	Up to 10 SpeedFusion Bonding License Key for MBX Mini
PVN-LC-20	Up to 20 SpeedFusion Bonding License Key for MBX Mini