



Peplink 221

5-in-1 cellular and W-Fi antenna system with GPS receiver

Features

- 5-in-1 cellular and W-Fi antenna system with GPS receiver
- 2x2 Cellular frequencies: 600-6000 MHz
- 2x2 Wi-Fi frequencies: 2400-2500 MHz & 5000-6000 MHz
- Durable and UV-stable housing
- Black or white color options
- IP67 rated



Overview

Antenna elements	2x LTE, 2x WIFI, 1x GPS
Cellular frequency bands	1.2dBi: 617-960MHz 5.7dBi: 1710-2700MHz 5.6dBi: 3400-4200MHz 6.0dBi: 5000-6000MHz
WIFI frequency bands	4.8dBi: 2400-2500MHz 7.4dBi: 5000-6000MHz
GPS frequency bands	1.6dBi, LNA 28dB: 1561-1602MHz
IP rating	IP67
Dimensions	(Height) 1.42" / 36mm (spigot not included) (Diameter) 5.12" / 130mm
Coax cable type	CFD-200 (4G/5G, Wi-Fi) RG-174 (GPS)
Connector Type	SMA male (4G/5G, GPS), RP-SMA male (Wi-Fi)

Description

The Peplink Puma-221 is a 5 in 1 antenna built for mobile applications. It supports 2x2 cellular MIMO for high bandwidth and solid reliability, dual-band (2.4GHz & 5GHz) Wi-Fi and GPS. It is also 5G ready and supports a wide range of global cellular frequencies. The GPS receiver is equipped with high gain LNA, making it ideal for location tracking.

The Puma-221 has a solid housing made of UV stable plastic materials. Two color options are available (black and white) to fit different deployments. For easier installation, the antenna comes with different cable length options.

Applications

- Public Safety and mission critical connectivity
- Mobile healthcare
- Transportation Connectivity

Contact Us

sales@peplink.com

Find a Peplink Certified Partner

<https://www.peplink.com/peplink-certified-partners/>

Puma 221



Specification

Cellular

Antenna elements	2 elements
Cellular frequency bands	1.2dBi: 617-960MHz 5.7dBi: 1710-2700MHz 5.6dBi: 3400-4200MHz 6.0dBi: 5000-6000MHz
VSWR	< 2.5 over 85% of the band
Feed power handling	10W
Input impedance	50 Ω
Polarisation	Linear

Wi-Fi

Antenna elements	2 elements
Peak gain	4.8dBi: 2400-2500MHz 7.4dBi: 5000-6000MHz
VSWR	< 2.5
Feed power handling:	10W
Input impedance:	50 Ω
Polarisation:	Linear

GPS

Frequency range	1561-1602 MHz
Peak gain	0.5dBi@1575MHz 1.6dBi@1602MHz
VSWR	< 2 dB
Output return loss	10dB max
Gain: LNA	28 $\pm$ 3dB
Noise figure	1.5dB max at 3.3V
Operating Voltage	3.3V
Power consumption	8.5 $\pm$ 2.5mA at 3.3V

Cable

Type	CFD-200
Loss	0.33 dB/m @ 900 MHz 0.49 dB/m @ 2000 MHz 0.55 dB/m @ 2500 MHz 0.87 dB/m @ 5800 MHz
Diameter	0.2" / 5.0mm
Jacket	Half matt PVC, UV resistant
Termination	SMA male and RP-SMA male
Type	RG-174
Loss	3.4 dB/m @ 1000 MHz 4.9 dB/m @ 1800 MHz
Diameter	0.1" / 2.7mm
Jacket	Half matt PVC, UV resistant
Termination	SMA male

Puma 221

Mounting

Supported types	Panel, wall, pole
Mounting hole	1 11/16" / 43mm
Max panel thickness	19/32" / 15mm

Mechanical

Product dimensions	(Height) 1.42" / 36mm (spigot not included) (Diameter) 5.12" / 130mm
Packaged dimensions	8.90" x 8.46" x 4.29" / 226 x 215 x 109mm
Radome material	UV stable PC+ABS

Package contents

Antenna	Puma 221
Mounting	Wall/pole mount Double sided 3M adhesive pad Diameter: 5.08" / 129mm Thickness: 0.08" / 2mm


Environmental, compliance

IP rating	IP67
Operating temperature	-40° - 176°F / -40° - 80°C
Storage temperature	-40° - 176°F / -40° - 80°C
Compliance	Complies with RoHS requirements
Salt Spray	MIL-STD 810F/ASTM B117
Solar Radiation	UL746C(f1)
Wind Survival	$\leq$ 220 km/h




Ordering information

Puma 221




Product Code	Description
PUMA-221-S-W-6	2xLTE, 2x Wi-Fi, 1xGPS 600-6000MHz, IP67, SMA/RP-SMA, White, 6.5ft / 2m
PUMA-221-S-B-6	2xLTE, 2x Wi-Fi, 1xGPS 600-6000MHz, IP67, SMA/RP-SMA, Black, 6.5ft / 2m
PUMA-221-Q-W-1	2xLTE, 2x Wi-Fi, 1xGPS 600-6000MHz, IP67, QMA, White, 1 ft / 0.3m
PUMA-221-Q-B-1	2xLTE, 2x Wi-Fi, 1xGPS 600-6000MHz, IP67, QMA, Black, 1 ft / 0.3m


Extension cable



LTE/GPS elements




Wi-Fi elements




Product Code	Element type	Description
EXC-SQ-15	LTE/GPS elements	Extension coax cable, SMA male to QMA female connector, 15ft / 4.5m
EXC-QQ-15	LTE/GPS elements	Extension coax cable, QMA male to QMA female connector, 15ft / 4.5m
EXC-RQ-15	Wi-Fi elements	Extension coax cable, RP-SMA male to QMA female connector, 15ft / 4.5m

Puma 221

Technical drawing



Puma 221




Index


No.	Description	Qty
1	Antenna top cover (PC+ABS)	1
2	Antenna bottom cover (PC+ABS)	1
3	Double sided 3M adhesive pad	1
4	Hexagon NUT (PC+ABS)	1
5	Cable CF2-200 (4G/5G, Wi-Fi)	4
6	4G/5G antenna connector	2
7	4G/5G cable marking	2
8	GPS cable marking	1
9	Label	1
10	Cable RG-174 (GPS)	1
11	GPS antenna connector	1
12	Wi-Fi cable marking	2
13	Wi-Fi antenna connector	2

Antenna VSWR

4G/5G




Wi-Fi




Puma 221

Antenna Gain

4G/5G




Wi-Fi




Puma 221

Antenna Efficiency


4G/5G



Wi-Fi




Antenna Isolation




Puma 221

Radiation patterns (Azimuth, LTE)


617-960 MHz



1710-2100MHz




2300-2700 MHz




Radiation patterns (Azimuth, LTE)


3400-3800 MHz



4200-5150 MHz




5350-5930 MHz




Puma 221

Radiation patterns (Azimuth, Wi-Fi)


2400-2500 MHz



4900-5350 MHz




5500-5950 MHz




Radiation patterns (Elevation 1, LTE)


617-960 MHz



1710-2100MHz




2300-2700 MHz




Puma 221

Radiation patterns (Elevation 1, LTE)


3400-3800 MHz



4200-5150 MHz




5350-5930 MHz




Radiation patterns (Elevation 1, Wi-Fi)


2400-2500 MHz



4900-5350 MHz




5550-5950 MHz




Puma 221

Radiation patterns (Elevation 2, LTE)


617-960 MHz



1710-2100MHz




2300-2700 MHz




Radiation patterns (Elevation 2, LTE)


3400-3800 MHz



4200-5150 MHz




5350-5925 MHz




Puma 221

Radiation patterns (Elevation 2, Wi-Fi)


2400-2500 MHz



4900-5350 MHz




5550-5950 MHz




Puma 221

Installation recommendation

Panel Mount



Puma 221




Notes


- Cover panel surface to protect the paint work. When drilling a hole, start with a small one, then increase it.
- Cut out diameter should be 1 11/16" / 43mm.
Maximum allowed panel thickness - 15mm.
- After a drill clean up the surface and apply some paint around the hole to prevent corrosion. Attach the antenna.

Installation recommendation

Pole Mount





Puma 221



Installation recommendation

Horizontal Pole Mount

Puma 221



Installation recommendation

Wall Mount

Puma 221

