

Ubiquiti PoE-48 PoE Adapter (POE-48-24W-KIT)



Product Name: Ubiquiti PoE-48 PoE Adapter (POE-48-24W-KIT)

Manufacturer: Ubiquiti Networks

Model Number: POE-48-24W-KIT

Ubiquiti PoE-48 PoE Adapter (POE-48-24W-KIT)

Please Note: We include a UK power supply with the POE-48 Adapter.

The Ubiquiti PoE-48 is a Power over Ethernet Adapter for use with your Ubiquiti Wireless Networking devices.

Ubiquiti POE-48 Key Features

- LAN Activity Indicator: Detects if LAN is connected to device
- Remote Reset Capability: Supports Airmax Bullet, Rocket, Nano, Pico

Ubiquiti POE-48 Technical Specifications

Power

- Output Voltage: 48VDC at 1.0A
- Input Voltage: 90-260VAC at 47-63Hz
- Input Current: 0.3A at 120VAC, 0.2A at 230VAC
- Inrush Current: $15A$ peak at 120VAC, $30A$ peak
- Efficiency: 70+%
- Output Ripple: 1% Max
- Switching Frequency: 200kHz
- Line Regulation: +/- 0.5%
- Load Regulation: +/- 1%
- Surge Protection: Common Mode
- Clamping Protection: 11V Data, 77.5V Power
- Max Surge Discharge: 1200A (8/20uS) Power
- Peak Pulse Current: 36A (10/1000uS Data)
- Shunt Capacitance: $5pF$ data
- Response Time: $1nS$

Interface

- AC Connector: IEC-320 C6
- Data In/POE RJ45 Shielded Socket
- 80% Current Indicator: Power LED will change color

Physical

- Operating Temperature: -10C to +60 C
- Storage Temperature: -20 to +85 C
- Operating Humidity: -10C to +60 C
- Size: (LXWXH) 85 x 55 x 33 (mm)
- Weight 4 oz

Certification

- Compliance UL, EN55022 (CISPR22) class B, Meets CE

Please visit the Ubiquiti Firmware page for the latest Firmware upgrades

Ubiquiti PoE-48 PoE Adapter (POE-48-24W-KIT)

Price: £10.00
